


# **BIESSE ACTIVEEDGE 60**

Semi automatic edgebanding machine



Minimum size,  
maximum performance



Made In Biesse

## Active Edge 60

is the new compact, semi-automatic edge banding machine for straight and shaped panels.

Plug & Play: It is very simple to install, operate and maintain.



- ✓ **Dual rollers: dedicated rollers for applying glue on edgebanding tape and straight panels**
- ✓ **Dual temperature system: Electronic PID temperature controller**
- ✓ **Quick change from straight edging operation to curved edging operation**
- ✓ **Precise automatic cutting of edges, thanks to smart PLC control using Encoder feedback**
- ✓ **Matrix table for easy handling of panels**
- ✓ **Variable speed: 3 - 12 m/min**

### Technical specifications

Description	Units
Panel height	10 - 60 mm
Min height of edgebanding material	14 - 64 mm
Thickness of edgebanding material in rolls	0.4 - 3 mm
Min edgebanding radius	25 mm (flat edgebanding 0.4 mm)
Min length of edgebanding material	350 mm
Working speed	3 - 12 m/min
Glue pot capacity	3 kg
Max diameter for edge loader	800 mm
Pneumatic connection	7 bar
Working voltage	400 V / 50Hz 3 phase + neutral

