

# BORDATRICE MONOLATERALE SERIE FAST F600-23 (con rettificatore)



Modello – Model - Modèle – Modell - Modelo	<b>F200-23</b>	<b>F400- 23</b>	<b>F600- 23</b>	<b>F650- 23 plus</b>
Spessore pannello - Panel thickness Espaisseur panneau – Werkstückdicke Espesor panel	10 ÷ 60 mm	10 ÷ 60 mm	10 ÷ 60 mm	10 ÷ 60 mm
Larghezza pannello – Panel width Largeur panneau – Werkstücklänge Largo panel	min. 60 mm	min. 60 mm	min. 60 mm	min. 60 mm
Larghezza bordo – Edge width Largeur chant – Kantenbreite Anchura canto	12 ÷ 63 mm	12 ÷ 63 mm	12 ÷ 63 mm	12 ÷ 63 mm
Spessore bordo – Edge thickness Espaisseur chant – Kantendicke Espesor canto	0,4 ÷ 6 mm	0,4 ÷ 6 mm	0,4 ÷ 6 mm	0,4 ÷ 8 mm
Avanzamento – Feed – Avancement – Vorschub - Avance	10 mt/min (STD)	10 mt/min (STD)	10 mt/min (STD)	12-16 mt/min (STD)
Voltaggio – Voltage – Voltage – Spannung - Voltaje	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N	220/380 V 50/60 Hz – 3 Ph + N
Lunghezza pannello – Panel length – Longueur panel – Werkstücklänge Largo panel	min. 120 (PVC)	min. 120 (PVC)	min. 120 (PVC)	min. 120 (PVC)
Potenza installata – Installed power – Puissance installée – Leistung installierte – Potencia installada	8,0 kw	8,0 kw	8,2 kw	8,2 kw
Potenza pneumatica – Pneumatic power – Puissance pneumatique – Leistung pneumatic – Potencia neumatico	6 bar	6 bar	6 bar	6bar
Peso kg – Weight Kgs. – Poids Kgs. – Gewicht Kgs. – Peso Kgs.	920	1000	1200	1200

