



SINCE 1946
GRIGGIO
WOODWORKING MACHINERY

GL150

LEVIGATRICE A NASTRO OSCILLANTE
OSCILLATING BELT SANDING MACHINE

CE
BASIC



Levigatrice a nastro oscillante / Oscillating belt sanding machine Schwingende bandschleifmaschine / Ponceuse à bande oscillante Lijadora de banda oscilante	GL 150
Dimensioni piano lavoro fisso / Sizes of fixed working table Abmessungen des festem Tisches / Dimensions table fixe Dimensiones de la mesa fija	mm 220 x 1440
Dimensioni piano lavoro inclinabile / Sizes of tilting working table Abmessungen des schraegst Tisches / Dimensions table inclinable Dimensiones de la mesa inclinable	mm 220 x 1440
Larghezza complessiva piani / Total lenght of the tables Gesamtlänge der Arbeitstische / Largeur totale des tables Dimensiones totales de las mesas	mm 700
Inclinazione piano / Tilt of the table Schraegverstellung / Inclination de la table Inclinacion de la mesa	0° - 45°
Altezza piani di lavoro / Height of working table Höhe der Arbeitstische / Hauteur des tables de travail Altura mesas de trabajo	mm 950
Sviluppo nastro abrasivo / Abrasive belt development Bandlaengenentwicklung / Développement de la bande abrasive Medida cinta abrasiva	mm 150 x 2200
Velocità nastro / Belt speed Schleifbandgeschwindigkeit / Vitesse de la bande Velocidad de la cinta	mt/sec. 12 / 8
Diametro rullo motorizzato / Motorized roller diameter Motorisierte Rolle Durchmesser / Diamètre rouleau motorisé Diametro rodillo motorizado	mm 160
Diametro rullo condotto / Driven roller diameter Leitungsrolle Durchmesser / Diamètre rouleau conduit Diametro rodillo conducto	mm 80
Potenza motore traino nastro / Belt drive motor power Bandvorschubmotorstaerke / Puissance moteur avance bande Potencia motor cinta transportadora	CV-HP 2,5 - 3,5 (KW 1,8 - 2,5)
Potenza motore oscillazione / Oscillation motor power Schwingenmotorstaerke / Puissance moteur oscillation Potencia motor para oscilar	HP 0,5
Corsa oscillante / Oscillating stroke Schwingenlauf / Course oscillante Recorrido oscilante	mm 20
Spostamento verticale gruppo oscillante / Oscillating vertical movement Vertikalverstellung Schwingaggregat / Déplacement vertical groupe oscillan Desplazamiento vertical grupo oscilante	mm 160
Diametro cappa aspirazione / Suction dust hood diameter Absaughaube Durchmesser / Diamètre hotte d'aspiration Diametro boca de aspiracion	mm 140
Pressione di esercizio / Working pressure Betriebsdruck / Pression d'exercice Presion de trabajo	6 bar.
Peso netto / Net weight Nettogewicht / Poids net Peso neto	kg 550
La ditta si riserva di apportare qualsiasi modifica o miglioria. Our Firm reserves the right to make any changes or improvements. Die firma Behält sich vor Änderungen oder Verbesserungen vorzunehmen. La maison se réserve d'apporter quelconque changements ou amelioration. Datos tecnicos son sin compromiso.	

