

# HIGH SPEED Router

**HIGH PRECISION  
ECONOMY  
FLEXIBILITY**



The best quality Overarm High Speed Router is with rigid body and without vibration.

The standard of HR5 can be separated during the shipment in order to save the packing cuft. Big shaft with high precise bearing ensures heavy duty routing.

**HR 5**

**HOLYTEK**

# HOLYTEK

## EFFICIENCY AND ECONOMY

### DESIGN FEATURE

- \* Pneumatic and easy changeable spindle unit
- \* 6 depth stop of adjustment
- \* Mechanical brake
- \* Air blowpipe
- \* Two speed 10,000/20,000 rpm of spindle
- \* Convenient air pedal control unit

### STANDARD EQUIPMENT

- \* Flat belt: 1 pc
- \* Table guide fence
- \* Collect: 1/4", 1/2"
- \* Router bit: 3/8"
- \* Guide pin: 3/16"-1/4", 5/16"-3/8", 7/16"-1/2"
- \* Plastic dust cover
- \* Grease gun
- \* Wrenches and hexagon keys
- \* Tilting table
- \* Hydraulic stabilizer control spindle

### SPECIFICATION

| MODEL                             |          | HR5           | HR7           |
|-----------------------------------|----------|---------------|---------------|
| Throat clearance                  | (mm)     | 500           | 650           |
| Spindle speed                     | (r.p.m.) | 10000/20000   | 10000/20000   |
| Spindle motor                     | (HP)     | 3             | 5             |
| Vertical stroke of spindle        | (mm)     | 100           | 100           |
| Clearance between chuck and table | (mm)     | 150           | 300           |
| Depth end stops                   |          | 6             | 6             |
| Table size                        | (mm)     | 610×460       | 750×600       |
| Overall dimensions                | (mm)     | 900×610×1730  | 1100×800×1600 |
| Packing size                      | (mm)     | 1060×710×1150 | 1400×900×1800 |
| N.W./G.W.                         | (kgs)    | 280/350       | 500/650       |

\* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.



HR5 Overarm Router Table can be tilted to 45° and extended up to 1010×660mm (on request)



**HR 7**

# HOLYTEK

**HOLYTEK INDUSTRIAL CORP.**

9F-1, NO.400, SEC.1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-22452818 (REP.) FAX: 886-4-22436928

E-mail: holytek@ms13.hinet.net

http://www.holytek.com.tw

© HT-200308