



P-32-3H



TECHNICAL SPECIFICATIONS

Sliding table cutting lengths	With or without scoring saw blade
2600 mm (102.36")	2500 mm (98.43")
3200 mm (126")	3100 mm (122.05")
3800 mm (149.61")	3700 mm (145.67")

CUTTING DEPTHS

Saw blade diameter	Ø250 (10")	Ø300 (12")	Ø350 (14")	Ø400 (16")
Cutting depths at 90°	0~50 mm (0~2")	0~75 mm (0~2.95")	0~105 mm (0~4")	28~125 mm (1.1~4.92")
Cutting depths at 45°	0~35 mm (0~1.38")	0~53 mm (0~2.09")	0~73 mm (0~2.76")	19.8~88 mm (0.8~3.5")

SPECIFICATIONS

Unit: mm

ITEM	MODEL	P-26-3H	P-32-3H	P-38-3H
Rectified cast iron fixed table dimension		570 x 1000		
Sliding table dimension		380 x 2600	380 x 3200	380 x 3800
Max sawing carriage Ø 355mm (14")		•		—
Sawing carriage Ø 400mm (16")		√		•
Main saw blade Ø305 mm (12")			•	
Main saw blade Ø355 mm (14")			√	
Main saw bore		Ø 30 (Ø 25.4)		
Max. cutting height with blade at 90 °		105		125
Max. cutting height with blade at 45 °		73		88
Main motor power 7.5HP (5.5 kw)			•	
Main blade speed		3000 / 4000 / 5000 rpm		
Scoring saw blade Ø 120			•	
Scoring saw blade bore			Ø 22	
Scoring motor power 1HP (0.75 kw)			•	
Scoring blade speed			8000 rpm	
Cutting width 1300 mm			•	
Cutting width 1500 mm			√	
Cutting width adjustment		CNC CONTROL		
Saw table extension 370 mm			•	
Saw table extension 720 mm (CE)			√	
Mitre fence			•	
Blade tilting adjustment		CNC CONTROL (0°~45°)		
Main saw height adjustment		CNC CONTROL		
Scoring saw height adjustment		MOTORIZED		
Scoring saw + / - direction adjustment		MOTORIZED		
Overhead saw guard		Luxurious		
Crosscut fence digital display			√	
Rip clamp			√	
Tool frame			√	
			• (CE)	
Dust collection system		Main chanel 4", Luxurious 3"		

■ Specifications subject to change without prior notice

• : STANDARD √ : OPTIONAL