



		223D	245D
Max. working length	mm	3200	4500
Max. cutting height (with 350 mm. diam. main blade)	mm	80	80
Max. dimensions of panels on platform	mm	3000x2200	4300x2200
Max. height of panel package on platform	mm	500	500
Max. distance of pusher from cutting line	mm	3200	3200
Feed speed of sawblade carriage	my/min.	13,5-27	13,5-27
Return speed of sawblade carriage	my/min.	27	27
Fast speed of pusher (feed and return)	my/min.	9	9
Slow speed of pusher	my/min.	0,4	0,4
Main blade speed	rpm	3700	3700
Scoring blade speed	rpm	8000	8000
Main blade motor power	HP	10	10
Scoring blade motor power	HP	1,5	1,5
Diam. of sawblade shafts	mm	30	30
Diam. of 2 dust extraction outlets	mm	120	120
Net weight (basic machine)	Kg.	4760	5750
Gross weight (basic machine)	Kg.	5750	5750
Dimensions of seaworthy packing case	mm.	5200x2400x2200	6550x2400x2500

MAIN OPTIONS. Anti-friction coated front steel tables - Front bakelite coated air filtration tables - Hydraulic speed variator for sawblade carriage stroke - Two-speed pusher 9/18 my/min. (9 my/min. forward - 18 my/min. return)

