

Code	Description
000691	FORTE 630
000691400	FORTE 630 CE



Thickening machine

Technical data

Net weight kg 805

Useful working width mm 630.

Worktable dimensions mm 900 x 630

Max working height mm 300.

Min working height mm 4.

Min workpiece length mm 280.

Max cutting depth mm 8.

Cast-iron table

N° 2 idle rollers on the table

N° 2 outfeed motor-driven rollers.

Complete with sound-proof material.

Table height-adjustment by 4 cylinders

Motor-driven lifting of the table with fine adjustment by electric pushbutton

Feeding speed 4 - 7 - 10.5 - 16.5 m/1'

Cutterblock diameter mm 120

4 cutters mm 630 x 30 x 3

Cutterblock rotation speed 5600 rpm

Lifting gear motor HP 0.33 (kw 0.25)

Digital read out for table positioning

Motor HP 7.5 (kw 5.5)

Accessories on request

085000	Motor power hp 10(kw 7,5)
734D00	Set of extra knives for standard shaft 630 mm
300E00	Tersa planer shaft 630 mm each
301E00	Set of 4 knives for tersa shaft 630 mm
090000	Sectionated tothed roller
736E00	Rubber rollers
201D00	Electronic digital-read out
960E00	Electronic inverter for feeding speed adjustment from 3 to 25 mt/min
903D00	Electronic programmer for the automatic vertical programming of the table. Possibility to store up 99 programmes. Possibility of selecting any table position in addition to 99 programmes. Possibility of correcting the position value for the selected programme. Safety limit switch for the automatic lifting
IMB691	Packing in wooden case
VLT691	2% increase for voltage different from 400/3/50
CSA691	Csa norms