



The CML Standard Series is tailored to meet from low to high volume production requirements. With the Standard Series, you get the features you need, without paying for extras you don't. The J250 series features a heavy-duty Multi-Rip saws with higher horsepower ratings for higher volume customers. The J350, SCA 320 T 350, SCA 450 T 500 and SCA 650 T 700 are heavy-duty machines with even more horsepower that provides a wider cutting area possibilities with an high volume environments. Whatever your requirements, Cml offers a Ripsaw to meet your needs.

CML

Cml has industry-leading ripsaws to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML multi-rip saws optimize materials and minimize costs. CML multi-rip saws deliver high quality cuts with limitless application possibilities. Whatever your requirements. CML has a ripsaws to help you make the most of every situation.

CML ENGINEERING S.R.L.
Advanced Equipment
Intelligent Integration
Experienced Consulting
Incomparable Services
E-mail [info@cml-engineering .it](mailto:info@cml-engineering.it)

Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 3 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft
- Easy and practical operation clearly displayed via the control panel
- Complete range of optimization solutions



Standard Series

Multi-Rip saws J250

Technical Specifications	CML Multi-Rip Saw J250
Voltage	400V / 50Hz
Dust Connection (MAIN)	200mm diameter port/30 meters per second/3400Mc3/h
Machine Weight	1200Kg
Machine Dimensions	Length 125cm Width 117cm Height 130cm
Main Drive Motor	Hp 20-25 / Kw 15-18.5
Feed Belt Motor	0.75Kw
Feed Belt Speed	12 a 24 Mt/1"
Pressure Roll Motor	0.75Kw
Maximum pass thru width	550mm
Feed belt width	250mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	80mm (300mm Blade)
Minimum board Thickness	20mm
Minimum board Length	500mm (280mm optional)
Maximum distance between fixed blades	220mm
Table working height from floor	750mm
Sound enclosure padding for quite running reducing noise level 15db	
Automatic oil pump for feed chain with failure detection shutoff	
Specifications are subject to change.	



Main Office : Via Torri Bianche 1 - 20059 VIMERCATE (MI) – ITALY

Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY

Tel 0039-02-95384207

Fax 0039-02-95384223

E-mail : info@cml-engineering.it – Web : www.cml-engineering.it