

OPTIMIZING CUT-OFF SAW GreCon 2004

The optimizing cut-off saw Model GreCon 2004 with its reliable and modern technique is easy to be operated; this is the ideal total optimizing cut-off saw for all woodworking companies.

Measuring station

 By means of light barriers and one pulse counter length of the timber, and by means of a scanner position of the crayon markings are measured precisely and then evaluated by the computer.

Transport and cut-off saw

- The sturdy electric feed unit (ACservomotor) guarantees extremely fast and precise positioning.
- By means of a combination of pressure rolls (with central height adjustment) acting from above and a conveyor chain, with powered outfeed behind the saw blade, processing of individual boards for sidings is ensured as well.
- The drive control permits precise cutting positioning at high speed.
- The conveyor chain forms measuring station and cut-off saw to a com-

plete unit, being very sturdy and absolute unsusceptible to trouble.

Computer cabinet

- It contains all switches necessary for operation as well as the computer rack for optimization, keyboard, screen.
- By means of this central unit, the complete line is controlled, ensuring distinct and easy operation.

Input and operation

Easy operation is effected via a keyboard guided by the menu technique. This special technique permits every operator to find the request presentation on the screen, e.g. the input data, the cutting orders and the current output data.

Working off of a cutting order can be shown on the screen at every time; simultaneously the results concerning cutting losses and waste achieved so far. A report concerning the current respectively the worked-off cutting order can always be shown on the screen or printed out.

Optimizing variables:

- according to the minimum cutting losses
- with priority evaluation of different lengths
- according to maximum price; a certain price is appointed to every position
- finger jointing program (minimum lengths)
- program for reusables
- selection concerning width measuring, qualities and thickness measuring
- diagnostic program for trouble shooting
- 3 D-rotation optimization
- integration of GreCon-SUPER-

SCAN is possible at any time Sorting

The requested sorting station is selected via keyboard.

Cutting order configuration

4 cutting orders with 20 lengths each are at disposal. Extension is possible.

Variations

2001 Saw for cutting defects

2002 Saw for cutting fixed lengths

2003 Computer-controlled cutting, giving preference to the longest cutting length Technical data

Feed speed Saw Blade Diameter Saw Motor A.C. Motor Drive **Dust Outlet** Working Height

0-140 m/min 500 mm 5.5 kW 7.5 kW 1×125 mm 860 mm







GreCon



Marking and buffer station

