The fully programmable compact machine - with a choice of three finish systems



SPRINT 1411 Edgebander

Compact edgebander designed to handle specific high production applications up to 13 mm. Three finish systems are available, all fully PCS - (Pneumatic Changeover Systems) controlled.

- PLC control system
- Patented cartridge glue system

Process:

- Coiled edging up to 5 mm
- Cut lengths up to 13 mm
- Workpieces from 6 to 45 mm thick



PLC control system

The HOLZ-HER PLC (Programmable Logic Control) ensures easy operation of all machining functions. The units can be selected individually. Units are graphically displayed, programs and error messages are shown in plain English. Experience constant, part-to-part, job-to-job accuracy with the HOLZ-HER PLC.

Patented glue application technology that offers unique advantages

Only HOLZ-HER gives you the patented cartridge glue system:

- Short heating-up times 75% faster than conventional systems
- Fast change of glue type and/or
- Closed heating system no vapors

The advantage:

The cartridge system is the only system that allows standard processing of EVA and PUR glue



PCS control systems


PCS - Pneumatic Changeover System controls cutting unit positions-controls end trim motor angle, changes top/bottom trimmers to flush or radius, positions scraper unit.

1411 Models

1411-2 (Super finish) End trim 2 flush trims Buffing 1411-3 End trim Flush trim Scraping Buffing 1411-4 (Super finish) End trim 2 flush trims Scraping Buffing



1411 Machine Units



Automatic edge feeder


• For coil edging up to 5 mm thick

Model 1901

Model 1942

Your authorized HOLZ-HER Special Machines dealer:

- Strip material up to 13 mm
- Extra large circular infeed table (820mm dia.)
- Patented tractor-belt feed



Cartridge Glue System


- Heat up time of 2 to 3 minutes
- Flat nozzle & thermostatic control glue application
- Connected power: 1.9 kW
- Automatic refill

Pneumatic Pressure Unit

Model 1913P

Model 1906

• Three rollers ensure a uniform, high contact pressure



End Trimming unit

Model 1918

6/45

51 350

180

11

0.4-13 mm*

- Edging thickness up to 13 mm
 For trimming front and rear projections
- Power 2 x 0.35 kW, 300 Hz
- Tilts 0-10°

Overall length

Edging thickness

Cut lengths, min. Workpiece width, min. Workpiece length, min.

Edging width, max. Edging length

Feed speed (m/min)

• Optional Pneumatic Changeover System


Sprint Technical specifications for 1411


Working dimensions, depending on equipment, in mm

SPRINT 1411 options -Buffing unit - plunge controlled 1944K (shown)

Workpiece thickness, min./max.


*with optional straight tooling






Flush Trimming Unit

- Edge thickness to 13 mm
- Flush
- Radius
- Chamfer (up to 15° tilt)
- Power: 2 x 0.6 kW, 300 Hz
- Optional Pneumatic Changeover System







- Edging thickness: 3 mm maximum
- PVC edging: 3 mm maximum (radius)
- Optional Pneumatic Changeover System

Buffing Unit

- For cleaning and edge chamfering
- 2 cloth wheels
- **Scraping Unit**
- Model 1929

- Tilting scope (up to 5° tilt)

-Chip collections box for scraper -PCS (Pneumatic Changeover System) -Varible track speed 11-16 m./min.



Specifications are based on approximate values.
All HOLZ-HER products are subject to ongoing innovation, therefore HOLZ-HER re-serves the right to to modify equipment designs, update any or all information and/or illustrations contained herewith. Illustrated models may also depict extends on the context. Model 1940

-Power raise/lower beam

also depict optional equipment. Contact your nearest HOLZ-HER distributor for exact specifications. For demonstration purposes, models shown may not feature their provided protective hoods.

HOLZ-HER

Corporate Office: 5120 Westinghouse Blvd. Charlotte, NC 28273 Tel.: (704) 587-3400 Fax: (704) 587-3419

Tel.: (909) 484-9181 Fax: (909) 484-9191 **Canadian Office:** Tel.: (800) 361-9367 Fax: (450) 963-7667 www.holzher.com

West Coast Office:



