



## BD-60

einseitig automatisch

- bohren
- Leim einspritzen
- Dübel eintreiben

single end automatic operation

- boring
- glue injecting
- dowel driving

machine automatique travaillant  
unilatéralement

- percer
- injecter la colle
- enfoncer les tourillons

## Technical Data for Standard Construction

[www.hoehsman.com](http://www.hoehsman.com)

Stock dimensions:	length	100–1000 mm (4" to 39")
	width	20– 600 mm (¾" to 24")
	thickness	10– 40 mm (¾" to 1–½")

### Traversing stock support table

### Boring Station

1 horizontal boring unit 1.65 kW (2.5 HP), ball-bushing guides, positive boring depth control by limit switch, equipped with multiple spindle boring head as specified

### Glue Injecting and Dowel Driving Station

Gluing/dowel driving tools	up to 6
Dowel diameters	6, 8, 8–8 mm (extra charge), 8–10 or 10–12 mm (¼", ⅝", ⅜" to ⅝", ⅝" to ¾", ¾" – 15/32")
Dowel length	30–40 or 40–50 mm (1–¼" to 1–½" or 1–½" to 2")
Dowel projection	7–14 or 15–25 mm (⅝" to ⅝" or ⅝" to 1")
Dowel centers	as boring spindle centers, up to 736 mm (29")

### Optional Equipment

- Automatic cleaning of glue injectors
- High pressure glue pump for waterproof glue or glue with higher viscosity
- Flexible manufacturing of individual orders