

FOUR SIDE MOULDERS

RAMBO 180 / 4

4 Spindles
Finished work piece min-max 16 - 180 mm

RAMBO 230 / 4

4 spindles
Finished work piece min-max 16 - 230 mm



TECHNICAL DATA

Finished Workpiece max. width	180 - 230 mm
Finished workpiece min. width	16 - 18 mm
Finished workpiece max. thickness	120 mm
Finished workpiece min. thickness	7 mm
Feeding speed	6 - 12mm
Pre-machined workpiece min. length:	
Single workpiece feeding	430 mm
Serial feeding	250 - 280 - 350 mm
Spindle rotation	6000 rpm
Diameter of first spindle	120 mm
Min. diameter of 2nd, 3rd, 4th, 5th spindle	180 mm
Horizontal spindles operating length	190 - 240 mm
Vertical spindles operating length	130 mm
5th spindle operating length	190 mm
5th spindle rotation angle	0 - 360°
Feeding rollers diameter	120 - 130 mm
Feeding table length	1700 mm
Table height from the floor	900 mm
Table and fence adjustment fence	10 mm
Horizontal spindles motor power 1st & 4th motor	7.5 Hp
Vertical spindles motor power 2nd & 3rd motor	10 Hp
Universal motor 5th	5.5 Hp
Feeding motor power	1.1 Hp
Total installed power	27 - 32 Hp



RAMBO 180 / 5

5 Spindles (4+1 universal)
Finished work piece min-max 16 - 180 mm

RAMBO 230 / 5

5 spindles(4+1 universal).
Finished work piece min-max 16 - 230 mm

