

## Numerically controlled router










For the more complicated production requirements or large and especially long parts (ie. caravan parts, lorry and boat mountings).

REICHENBACHER offers the type RANC-P with motions in X-direction of 2860 mm and 4000 mm and a working length up to 13000 mm. Noteably, it is the solid machine construction of this type that permits the use of

all working aggregates in any desired variation - outstanding

for this type.

Different table designs are available. The fixed table accessible from 3 sides offers the customer many possibilities for feeding and removing the parts, (an optional facility for an in-dependent roller infeed table is available for heavy components).



## Numerically controlled router

equipment of machine with 2 milling motors and special bearing of spindle

each motor is provided with a tool changer (for 16 tools, max. 200 mm Ø) for vertical work

 1 sawing aggregate with numerically controlled rotational axis

- 2 static inverters

- axis motions X-axis 2860 mm Y-axis 4700 mm Z-axis 400 mm

control Siemens Sinumerik 3M/4





Machine Type	y-stroke	a	b	weight
RANC 516 P	1600	2900	3200	ca. 12 t
RANC 523 P	2300	3600	4200	ca. 13 t
RANC 535 P	3500	4800	5400	ca. 15 t
RANC 547 P	4700	5900	6700	ca. 17 t
RANC 559 P	5900	7200	8200	ca. 20 t

