



This is the new model of the old and successfull sanding machine for moulding R3, with a new design but keeping the quality of our products (RESINFER is a company certified by the International Quality System ISO 9002).

With this model you can sand the 3 sides of the mouldings at the same time, due the machine is provided with:

- Two sanding groups on the top, that go up & down and tilt in order you could sand pieces with different type of moulding.
- different type of moulding.
  One sanding group in each side that can be put near or moved away from the moulding in order to get the suitable finish.

The above-mentioned motions are done from the electric control panel. This machine can be adjusted from the electric control panel in order we could work in two ways:

- With manual pressure
- With continuos and automatic pressure

Teh pieces pass over the machine on a dragging belt, which speed of working can be adjusted from 4 to 25 meters/minute.

We can sand pieces which wide was from 5 mm. to 160 mm. The maximun high of the pieces is 80 mm. this measures is taken having as reference one brush of diameter 200 mm.

The machine includes pressure wheels; adjusting these wheels we could sand small pieces.

Each sanding group is covered with dust-protections, in this way you could connect a dust extraction machine up and remove the sand.

Teh pieces pass over the machine on a dragging belt, which speed of working can be adjusted from 4 to 25 meters/minute.

We can sand pieces which wide was from 5 mm, to 160 mm. The maximun high of the pieces is 80 mm, this measures is taken having as reference one brush of diameter 200 mm.

The machine includes pressure wheels; adjusting these wheels we could sand small pieces.

Each sanding group is covered with dust-protections, in this way you could connect a dust extraction machine up and remove the sand.

## TECHNICAL DATA

Wide: 1.350 mm. Long: 2.220 mm. Tall: 1.500 mm Total Power: 7,5 H.P Weight: 550 kg.



