

Code	Description
000G41	SFL 1000 M
000G41400	SFL 1000 M CE



Spindle moulder with extended tables

Technical data

Net weight: kg 650

Spindle moulder with extended table mm 2500

Worktable mm 2500 x 825

Grounded cast-iron table

Adjustable aluminium fences.

Aluminium hood with micrometric guide adjustment and digital read-out with handwheel for fence adjustment

4 rotation speeds 3500-6500-8000-10000 rpm.

Max tool diameter mm 250 for profiling.

Vertical spindle stroke mm 180.

Vertical stroke mm 150, CE norms

Double bearings preloaded for high speeds

Self-braking motor (10")

Spindle safety guard.

Suction hood diameter 120 mm

Motor HP 5.5 (kw 4)

Electrical lifting of the table with mechanical read out digital read out

Registrable table in order to bring nearer the tool.

Accessories on request

403D00	Ce norms wiring (overload and emergency button)	CE included
906D00	Protection for working at the spindle	CE included
14C000	Motor power hp 7,5 (kw 5,5)	
675D00	Motor power hp 10 (kw 7,5)	
096000	Interchangeable mk5 spindle	
097000	Mk5 additional spindle	
228E00	Collets for mk5 spindle	
435D00	Additional mk5 spindle complete of nut for collets	
100000	Rotation's inverter (not available with mk 5)	
134F00	Digital read out	
251D00	Electronic programmer with microprocessor for the vertical movement of the spindle. Possibility to memorize up to 99 programmes. Possibility of selecting any spindle position in addition to the 99 existing programmes. Unit sliding on ball bearing screw hanging and turning on the control switchboard. Hanging and turning switchboard.	
263E00	3 axis electronic control:rise and fall of the vertical shaft, fence movement in entry of the hood of the spindle moulder. Possibility to programs up to 99 programmes,vertical sliding of the shaft on ball bearing screws. Hanging and turning switchboard.	
173E00	ledge-recovery unit: 6000 rpm with motor 3 hp (kw 2,2) with trapezoidal belts transmission, shaft diam.30 mm, positioning of 60 mm through 4 positions. Horizontal positioning of 50 mm with chuck. Supplied separately and without installation.	
459D00	Aigner type fence for spindle moulder's hood.	
227E00	Automatic star delta switch	
499D00	P rearrangement for feeder "fm"	
898E00	Quick rotating system for the exclusion of the protection hood from the table	
IMB211	Packing in wooden case	

Code	Description
VLT211	2% increase for voltage different from 400/3/50
CSAB04	Csa norms
189F00	Pensile x comandi
210F00	Posizionatore elettronico qem
191F00	Inverter 800-10000 giri