

KONTOUR

TORNI PER LEGNO

WOOD LATHES



KONTOUR 1200/CA



DATI TECNICI – TECHNICAL DATA – DONNEES TECHNIQUES

KONTOUR

1200 (1500)

Altezza punte Height of centres Hauteur pointes	mm	240
Distanza fra le punte Distance between centres Distance entre pointes	mm	1200 (1500 optional)
Motore mandrino Spindle motor Moteur mandrin	kW (HP)	1,1 (1,5)
Velocità di rotazione Revolving speed Vitesse de rotation	RPM	600 – 1000 – 1500 – 2000
Cono mandrino e contropunta Spindle and centre cone Cône Morse broche et contre-pointe		MK 3
Peso netto approssimativo Approx. net weight Poids net approx.	kg	250 (270)

●Dotazione: appoggia sgorbia 350mm, mandrino trascinatore 25mm, contropunta girevole ●Equipment: gauge rest 350mm, driving plate 25mm, revolving tailstock ●Equipement: appui gouge 350mm, entraîneur 25mm, contrepointe tournante



SS Romana Nord 41 - 41012 CARPI (Mo) – ITALY
Tel. +39-059-68.67.71 Fax +39-059-68.17.74
e-mail steton@steton.it www.steton.it