QUOTATION

on

ANDERSON CNC ROUTER

MODEL: STRATOS PRO XL

equipped with

1 x 10 HP ANDI HSK 63 (Air Cooled) Router Head with
1x 10-Tool Carousel with fast servo drive

1x 5+5 spindle boring block

Model: STRATOS/PRO XL



Basic Specifications

1. Working table:

- 3,700 x 2,100 mm



2. Working stroke:

X: 3,900 mmY: 2,750 mmZ: 350 mm

3. Speed:

- RT:

X: 80M/Min.Y: 45M/Min.Z: 30 M/Min.



- Feed rate: 24 M/min.

4. Spindle:

- One x 10 Hp Andi HSK-63F
- 24,000rpm
 One 10-tool carousel.
 Fanuc servo drive



5. Boring Block:

- One Boring block (5 x 5 vertical drilling)
- No horizontal (this is option)
- The distance between spindles is fixed.



6. Controller:

ANDI-FANUC 0i Controller + PC front end

- The length of program memory is 320M

(128KB)

- PC front end feature:
 - PC hardware will be provided by

Anderson.

- OS system : WINDOWS XP

- LCD monitor

- RAM: 256kb

- CD ROM

- Serial port

- USB

7. Clamping system:

- Vacuum pump : 3 x 250CBM

Power----- 10 HP

Capacity ----- 250 cbm


Pressure ----- 27.7" Hg





8. Miscellaneous:


- All spindles cover working table.
- The driven system:
 - X: rack & pinion system with two servomotors controlled.
 - Y: ballscrew system
 - Z: ballscrew system
- One set of light barrier is included.
- 10 Tool holders and collets are included.







- Handheld control interface
- Safety hood for spindle carrier.
- Touch-off function.
- Automatic tool height setting.



Included:

- Lifter/Loader system:



- Push & Dust Device:



- Scissor Lift:



- Conveyor Outfeed Table



- Automatic Label printer and loader system