

Wide belt sanding machine Boere

Sandonomic



Sandonomic

Top sanding wide belt sanding machine for calibrating and fine finishing, equipped with combi unit (C) or with a contact roller and combi unit (KC)

- Electronic-pneumatic sanding belt oscillation system
- Protection against running off of the sanding belt
- Pneumatic sanding belt tension
- Automatic brake device on the sanding unit
- Simple and quick replacement of the sanding pad
- Feed by means of a conveyor belt
- Rubber pressure rollers
- Electromotive height adjustment feed table
- Electronic digital counter for precise height adjustment feed table
- Manual precise height adjustment feed table
- Limit switches highest and lowest position feed table
- Protective finger guard
- Emergency stops in- and outfeed side
- Manually operated switches
- Thermal overload protection motors
- Ammeter sanding belt motor

Possible options :

- Heavier sanding belt motor
- Infinitely variable feed speed
- Extended feed table
- Simple sensor
- Steel contact roller
- Brush unit with cleaning brush



Boere Machinefabriek bv
 Brugweg 121, 2741 LA
 P.O. Box 8, 2740 AA
 Waddinxveen, NL
 T +31(0)182.614400
 F +31(0)182.618349
 E info@boere.nl
 I www.boere.nl

	Basic C-model	Basic KC-model
Sanding width	650 - 1300 mm	650 - 1300 mm
Sanding height	3 - 160 mm	3 - 160 mm
Sanding belt dimensions	660 - 1310 x 1900 mm	660-1310 x 1900 mm
Sanding belt motor	5,5 - 11 kW	5,5 - 11 kW
Height adjustment motor	0,25 kW	0,25 kW
Feed motor	0,3/0,55 kW	0,3/0,55 kW
Feed speed	4,5 + 9 m/min	4,5 + 9 m/min
Exhaust hood	ø 150 mm	2x ø 150 mm
Exhaust capacity	2500 - 4000 m ³ /hour	2500 - 4000 m ³ /hour