

# HOLYTEK

## SLIDING PANEL SAW P305



♦ Quick and secure locking wood pressure



♦ Miter fence with 0° to 45° adjustment for small cutting jobs (optional)



♦ Overhead saw blade guard (optional)



♦ Efficient dust collection system

### SPECIFICATIONS

ITEM	Model	P305 2,500 mm	P305 3,200 mm
Sliding table dimension		2,500 x 360	3,200 x 360
Cast iron table		548 x 896 mm	548 x 896 mm
Extension table (rear)		952 x 896 mm	952 x 896 mm
Extension table (front)		320 x 830 mm	320 x 830 mm
Table size		1,500 x 1,726 mm	1,500 x 1,726 mm
Round rail		φ 40	φ 40
Main saw blade (Max.)		305 mm (355 mm)	305 mm (355 mm)
Main saw bore		30 mm	30 mm
Max. cutting height with blade 305mm at 90° (355 mm)		90 mm (115 mm)	90 mm (115 mm)
Max. cutting height with blade 305mm at 45° (355 mm)		62 mm (70 mm)	62 mm (70 mm)
Main motor power (3 ph)		5 HP (3.75 kw)	5 HP (3.75 kw)
Main blade speed		4,000 r.p.m.	4,000 r.p.m.
Scoring saw blade		120 mm	120 mm
Scoring saw blade bore		20 mm	20 mm
Scoring blade motor power (optional)		3/4 HP (0.56 kw)	3/4 HP (0.56 kw)
Scoring blade speed		8,000 r.p.m.	8,000 r.p.m.
Cutting width		1,300 mm	1,300 mm
Main saw blade tilting adjustment		Manual (0°~ 45°)	Manual (0° ~ 45°)
Saw guard		Simple (overhead guard optional)	Simple (overhead guard optional)
Dust collection system		120 mm / 60 mm	120 mm / 60 mm
N.W./G.W./MEAS. (machine)		500/600 kgs (2,110 x 1,130 x 1,120 mm)	500/600 kgs (2,110 x 1,130 x 1,120 mm)
N.W./ G.W./ MEAS. (sliding table)		69/75 kgs (2,610 x 430 x 240 mm)	80/103 kgs (3,300 x 430 x 220 mm)
N.W./ G.W./ MEAS. (overhead guard)		39/40 kgs (1420 x 980 x 120 mm) + 1 / 2 kgs	640 x 210 x 210 mm)
Ctn. Q'ty:		9/19 sets	8/19 sets

# HOLYTEK

HOLYTEK INDUSTRIAL CORP.  
 9F-1, NO. 400, SEC. 1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.  
 TEL: 886-4-2245-2818(Rep.) FAX: 886-4-2243-6928  
 E-mail: holytek@ms13.hinet.net http://www.holytek.com.tw