

Ultra + 45

DOUBLE MITRE SAWS WITH BORING UNITS

HEAD UNITS ROTATION (+90° - 0 - 45) - DOUBLE INCLINATION OF THE BLADES

SOME TECHNICAL DETAIL

Mobile head cutting unit with motorized positioning by gear motor and electronic digital display. The sliding movement is made on tempered guides and ball recirculation racks

N.2 saw units with tilting blades Ø 400mm.: each unit equipped with KW.3 motor

N.2 support tables pieces supplied with pneumatic vertical and horiz.clamps

N.1 Intermediate support table

Rotation degrees reading by electronic digital display

N.2 Boring units supplied with heads at 3 mandrels interaxe of 32 mm (or other sizes on request) - Motors of Kw. 1,5 (r.p.m. 5500)

Sliding movement on rolling slide units

Mechanical reader for vertical and horizontal adjustments

Alternative cuts possibility

Start cycle by push button (by two hands as per Safety Regulations)

Rotation system of the units for frontal boring

Max. Height of the cut with blade at 90°	mm.	120	
Max. Height of the cut with blade at 45°	mm.	80 (external) -	mm. 45 (interior)
Max width of the cut	mm.	210	
Max width of the cut with head units at 45°	mm.	150	
Max. length of the cut	mm.	3.100	
Minim. Length of the cut : with blades at 90°	mm.	220	– with blades at 45° interior mm.870
Machine executed according to CE rules			