

Advanced Series

Multi-Rip saws SCA 650 T 700



The CML Advanced Series is tailored to meet from low to high volume production requirements. With the Advanced Series, you get the features you need, without paying for extras you don't. The SCA 650 T 700 series features a heavy-duty Multi-Rip saws with higher horsepower ratings for higher volume customers. Advanced Series machines includes others horsepower that provides different cutting area possibilities with an high volume environments. Whatever your requirements, Cml offers a Ripsaw to meet your needs.

CML

Cml has industry-leading ripsaws to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML multi-rip saws optimize materials and minimize costs. CML multi-rip saws deliver high quality cuts with limitless application possibilities. Whatever your requirements. CML has a ripsaws to help you make the most of every situation.

Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 6 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft
- Easy and practical operation clearly displayed via the control panel
- Complete range of optimization solutions

CML ENGINEERING S.R.L.
Advanced Equipment
Intelligent Integration
Experienced Consulting
Incomparable Services
E-mail info@cml-engineering.it



Advanced Series

Multi-Rip saws SCA 650 T 700

| | |
|---|--|
| Technical Specifications | CML Multi-Rip Saw SCA 650 T 700 |
| Voltage | 400V / 50Hz |
| Dust Connection (MAIN) | 300mm diameter port/30 meters per second/7600Mc3/h |
| Machine Weight | 6500Kg |
| Machine Dimensions | Length 255cm Width 245cm Height 200cm |
| Main Drive Motor | Hp 60-75-100-125 / Kw 44-55-74-92 |
| Feed Belt Motor | 3Kw |
| Feed Belt Speed | 0 to 36 Meters per minute |
| Pressure Roll Motor | 0.75Kw |
| Maximum pass thru width | 1150mm |
| Feed belt width | 700mm |
| Maximum Balde speed | 3500 RPM |
| Maximum board Thickness | 150mm (450mm Blade) |
| Minimum board Thickness | 20mm |
| Minimum board Length | 750mm (400mm) |
| Maximum distance between fixed blades | 650mm |
| Table working height from floor | 780mm |
| Sound enclosure padding for quite running reducing noise level 15db | |
| Automatic oil pump for feed chain with failure detection shutoff | |
| Specifications are subject to change. | |
| | |
| | |
| | |
| | |
| | |



Main Office : Via Torri Bianche 1 - 20059 VIMERCATE (MI) – ITALY
Production : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY
Tel 0039-02-95384207
Fax 0039-02-95384223

E-mail : info@cml-engineering.it – Web : www.cml-engineering.it