

PINTA 2500 FEED THRU CLAMP



FEATURES:

- Possible to assemble 1200 boxes in 8 hours at full speed.
- Sequenced-assembly of different furniture pieces without hand-preparation.
- Automatically adjusts both for height and length with photoelectric cells and encoders.
- Pressure supplied by electromotors
- Possibility of adjusting the pressing strength, both vertical and horizontal.
- All electrical and PLC components are Siemens.
- Silent design, low energy consumption (2Kw/hour).
- Cycle duration timer.
- Does not require extensive maintenance.
- The machine and electric system are manufactured in compliance with CE standards.

TECHNICAL SPECIFICATIONS:

- Max. Clamping length 2500 mm (98.4")
- Min. Clamping length 140 mm (5.5")
- Max. Clamping height 1250 mm (49.2")
- Min. Clamping height 250 mm (9.8")
- Max. Clamping width 620 mm (24.4"*)
- Worktable height 700 mm (27.6")
- Vert. & Horz. pressure 0-1200 Kg (0-2645lbs)
- Voltage 400vac 3phase 50Hz
- Installed power 4 KW (5.5 Hp)
- Weight 2450 Kg (5400lbs)
- Transport dimensions 4500x1500x2400mm (L x W x H) 177"x 59"x 94.5"

OPTIONS:

- Infeed and outfeed conveyor
- NC Center pressing bars
- Automatic clamping of cabinets with overhanging top



Automatic Raiser



Belt Conveyor