

of plates

Sizing and Edge

Trimming

**Assembly** 

Inserting and Packaging

patent pending AZ 20 2010 002 285.1



## **ZHR 340 BOOMERANG®** Return Conveyor

Return conveyor for the one-man operation at one-sided edge-banding machines. Thanks to an improved air-cushion table and a modified taking-over, the range of parts is enormously increased

- · Large variety of parts
- · Optimum part handling thanks to an aircushion table without ball valves
- · High capacity also in case of small workpiece gaps

- Pusher for capacity increase in a new
- Belt cleaning (simple) included in the standard
- · New safety equipment

**ZHR 30** 

**ZHR 540** 

**ZHR 340** 

ZHR 05

ZHR 02

ZHR 01



LIGMATECH Automationssysteme GmbH Phone: +49 37323 160 info@ligmatech.de · www.ligmatech.de



## ZHR 340 BOOMERANG<sup>®</sup> Return Conveyor

Workpieces coming from the basic machine are taken by outfeed belts running synchronously to the basic machine and then transported to an air-cushion table.

For stabilization, especially for small parts and for cross processing of larger parts, the supplied top pressure device is used.

By means of a pusher and the inclination of the air-cushion table the workpieces slide onto a transport belt and are transported on this belt. At the end of the return system the workpieces are fed to the operator on a non-driven roller conveyor.

For the flexible use, the machine can be operated in four standard work modes:

- air-cushion table always lowered without pusher operation
- air-cushion table always lowered with pusher operation
- air-cushion table in lifting operation (at top during pickup, then lowering) with pusher operation
- air-cushion table always at top for manual pick-up (no return of workpieces)

	2510		6000	-	
					-
	<u>-</u>				1210
	W 9111111111111111111111111111111111111	···· <del>···</del> ·····························	T F		1405
+ +	1217	8.660.01			-
1139		1 888081			_
, 1		5260	276	0	
	,		•		

	ZHR 340
Longitudinal throughfeed*:	
Part length	240 - 2,700 mm
Part width	60 - 1,000 mm
Cross throughfeed*:	
Part length	80 - 1,000 mm
Part width	240 - 2,500 mm
Part thickness	8 - 80 mm
Part weight	max. 50 kg
Working height	820 - 980 +/- 30 mm
Feed speed	8 - 30 m/min
Control	Eaton EASY

<sup>\*</sup> Larger parts can be returned or even fed out at 4-sided processing with manual support during crosswise offset and turning.



- 1 CE package
- Pneumatic air-cushion table for ramp
- Small-roller gibs to support wide parts
- Belt cleaning equipment

other options, see Price list



CE package



Pneumatic air-cushion table for ramp



Small-roller gibs to support wide parts



Belt cleaning equipment



lifeline | service

• eparts

Spare parts ordering online - around-the-clock!

Ligmatech Automationssysteme GmbH 03/2014