


COMBINATA FILO - SPESSORE  
 SURFACE PLANING AND THICKENING MACHINE  
 ABRICHT - UND DICKENHOBELMASCHINE  
 COMBINÉE RABOTEUSE - DEGAUCHISSEUSE  
 COMBINADA REGRUESADORA - CEPILLADORA



<b>DATI TECNICI</b> <b>TECHNICAL DATA</b> <b>TECHNISCHE DATEN</b>		<b>AD 530 SUPER</b>		<b>DONNES TECHNIQUES</b> <b>DATOS TECNICOS</b>	
Lunghezza piani Length of tables Tischlänge	mm mm mm	2300		Longueur tables Longitud mesas	mm mm
Velocità albero pialla Cutterblock speed Wellendrehzahl	g/min rpm U/min	4800		Vitesse arbre raboteur Velocidad eje	tr/1' g/min
Diametro albero pialla Cutterblock diameter Messer-Welle	mm mm mm	120		Diamètre arbre raboteur Diametro eje	mm mm
4 coltelli 4 Knives 4 Messer	mm mm mm	530 x 35 x 3		4 couteaux 4 cuchillas	mm mm
Guida inclinabile 45° Fence tilting 45° Abrichtanschlagschwenkung 45°	mm mm mm	1200 x 200		Guide dégaug inclinable 45° Guia cepillo inclinable 45°	mm mm
Larghezza max. piallabile Max. planing width Abrichtbreite	mm mm mm	530		Largueur de coupe Ancho max. de cepillado	mm mm
Dimensioni piano Table dimensions Tischgröße	mm mm mm	530 x 930		Dimensions de la table Dimensiones plano	mm mm
Spessore max. piallabile Max. thickening capacity Hobelhöhe max.	mm mm mm	3/250		Epaisseur max degauchissable Capacidad max. de cepillo	mm mm
Asportazione max. Max. depth of cut Spanabnahme max.	mm mm mm	8		Enlèvement maximum Espesor max. por pasada	mm mm
Velocità avanzamento Feed speeds Vorschubgeschwindigkeiten	m/min m/min m/min	7-11-15-19		Vitesses d'avancement Velocidades de avance	m/min m/min
Potenza motore Motor power Motorstärke	HP/KW HP/KW PS/KW	5,5/4		Puissance du moteur Potencia motor	CV/KW HP/KW
Emissione rumore Noise level Lärmemissionwert	db (A) db (A) db (A)	82,1		Pression acoustique Emision de ruido	db (A) db (A)
Peso netto Net weight Nettogewicht	kg kg kg	750		Poids net Peso neto	kg kg
Dimensioni imballaggio Packing size Verpackungsmasse	mm mm mm	2300 x 920 x 1000		Dimensions emballage Dimensiones embalaje	mm mm



COMBINATA FILO - SPESSORE

SURFACE PLANING AND THICKENING MACHINE

ABRICHT - UND DICKENHOBELMASCHINE






COMBINÉE RABOTEUSE - DEGAUCHISSEUSE

COMBINADA REGRUESADORA - CEPILLADORA

**AD 530 SUPER**

www.hoechsmann.com

**AD 530 SUPER**

-  DOTAZIONE STANDARD
-  STANDARD EQUIPMENT
-  STANDARD AUSRÜSTUNG
-  DOTATION STANDARD
-  EQUIPAMIENTO DE SERIE

# AD 530 SUPER



- VERSIONE
- EQUIPMENT
- AUSFÜHRUNG
- EQUIPEMENT
- EQUIPAMIENTO

-  SU RICHIESTA
-  UPON REQUEST
-  SONDERZUBEHÖR
-  SUR DEMANDE
-  SOBRE PEDIDO



Sollevamento automatico spessore  
Automatic thicknessing-table lifting  
Automatische Dickeneinstellung  
Table du rabotage  
Subida automatica regruesadora



Registralcoltelli magnetico  
Magnetic knife adjuster  
Magnetische Messereinstellehre  
Appareil magnetique de réglage des couteaux  
Regulador de cuchillas magnetico

Apertura automatica piane filo  
Automatic opening of planing tables  
Automatische Aufklappen der Abrichttische  
Ouverture automatique des tables  
Abertura automatica de las mesas del cepillo



Cavatrice pesante in ghisa  
Cast-iron mortiser  
Langlochbohrapparat (Schwere Ausführung)  
Mortaiseuse type fonte  
Taladro pesado en fundicion



Albero MONOBLOC Tersa con n° 4 coltelli  
MONOBLOC Tersa shaft with 4 knives  
Tersa Welle MONOBLOCK mit 4 Messer  
Arbre Tersa MONOBLOC avec 4 couteaux  
Eje Tersa MONOBLOC con 4 cuchillas