

Alberti Engineering

T-FLIGHT



NEW



DATI TECNICI

T-FLIGHT

TECHNICAL DETAILS

DIMENSIONI MASSIME DEL PANNELLO	mm	1800 x 900	WORKING MAX DIMENSIONS
DIMENSIONI MINIME DEL PANNELLO	mm	300 x 120	WORKING MIN DIMENSIONS
SPESSORE LAVORABILE	mm	12/55	PANEL THICKNESS
VELOCITA' MASSIMA PROGRAMMABILE:			PROGRAMMABLE MAX SPEED:
Asse X	m/min.	95	Axis X
Asse Y	m/min.	40	Axis Y
Asse Z	m/min.	55	Axis Z
Asse W	m/min.	14	Axis W
TOLLERANZA SU POSIZIONAMENTO ASSI	mm	+/- 0.1	TOLERANCE ON AXIS POSITIONING
POTENZA MOTORE MANDRINI	KW	1.5 - 3660 r.p.m.	SPINDLES MOTOR POWER
MANDRINI VERTICALI	n°	10 [X] + 8 [Y] Step 32 mm	VERTICAL SPINDLES
MOTORE LAMA Ø 150 mm	KW	1.5	SAW MOTOR Ø 150 mm
UNITA' INVERTER	KW	7.5 - 1000/18000 r.p.m.	INVERTER
ELETTROMANDRINO	KW	6.7	ELECTROSPINDLE
VELOCITA' ROTAZIONE ELETTROMANDRINO	r.p.m.	9000/18000	ELECTROSPINDLE ROTATION SPEED
DIAMETRO MASSIMO UTENSILE	mm	20	TOOL MAX DIAMETER
MASSIMA POTENZA RICHIESTA	KW	18	MAX INSTALLED POWER
PRESSIONE DI ESERCIZIO	bar	6/7	COMPRESSED AIR WORKING PRESSURE
CONSUMO	N/Ciclo	100	CONSUMPTION
VELOCITA' ARIA ASPIRANTE	m/s	30	DUST EXTRACTION SPEED
CONSUMO ASPIRAZIONE TRUCCIOLI	m³	3137	DUST EXTRACTION POWER
PESO TOTALE	Kg	1300	TOTAL WEIGHT
DIMENSIONI INGOMBRO	mm	3000 X 1920 X 2000	MACHINE OVERALL SIZE
PROTEZIONI NORME CE			CE SAFETY PROTECTION
RETE METALLICA 4 LATI			4 SIDES PROTECTION



Via Galileo Galilei, 34/36 - 20060 Gessate (MI) Italy - Tel. +39 02 95 78 19 999 - Fax +39 02 95 38 3791
 E-mail: info@albertiengineering.com - www.albertiengineering.com

