

THROUGH FEED PRESS

Through feed press to perform the coating of boards and panels with veneer, HPL, and other material son both sides.

This machine has a touch screen for control and implementation through which we can adjust time, temperature and pressure of work.



MODEL PCC 1638

TALLERES MECÁNICOS MARCH, S.L.

Ave. Miguel Hernández, 25 - 46960 ALDAIA - VALENCIA - SPAIN

TEL. +34 96 150 14 06 - FAX. +34 96 150 16 04

E-mail: march@tmarch.com

www.tmmarch.com

PCC

MARCH®



SPECIFICATIONS

MODEL	PCC1431	PCC1452	PCC1480	PCC2080	PCC2260	PCC2657
Plates (mm.)	1.400x3.100	1.400x5.200	1.400x8.000	2.000x8.000	2.200x6.000	2.600x5.700
Cylinders	8	12	20	30	24	24
Ø cylinders	125 mm.	125 mm.	125 mm.	140 mm.	140 mm.	140 mm.
Opening	120 mm.	120 mm.	120 mm.	120 mm.	120 mm.	120 mm.
Specific pressure	6 Kg/cm ²	6 Kg/cm ²	6 Kg/cm ²	8 Kg/cm ²	8 Kg/cm ²	7 Kg/cm ²
Total pressure	225 Tn	338 Tn	564 Tn	1.061 Tn	849 Tn	849 Tn
Hydraulic system	3 kw.	4 Kw.	7,5 Kw.	18,5 Kw.	15 Kw.	15 Kw.

We can manufacture other models under demand

www.tmmarch.com