Sergiani gs press with electronic control and manual loading/unloading





sergiani gs

press with electronic control and manual loading/unloading

Structure quality

The sturdy structure has been engineered with a high safety coefficient to guarantee the highest level of resistance and rigidity in each processing phase. The **new GS range** designed to meet all customers needs: the best choice for panels and doors pressing.

The wide range of models and configurations suits every production requirement.



Hydraulic cylinders
The steel rod is chromed
with a thick layer and
rectified, all gaskets are high
resistance to guarantee long
lifetime and perfect seal.

Control panel with siemens colour touch screen

The new control panel is equipped with a software that allows to automatically calculate the hydraulic pressure, manage the heating system, carry out a complete diagnostic, program and save all working parameters.

TECHNICAL DATA					
Model	Platens dimensions	Total thrust (ton)	Model	Platens dimensions	Total thrust (ton)
GS 4/20	2500X1300	20	GS 6/120	3100x1600	120
GS 4/60	2500x1300	60	GS 6/90	3500x1300	90
GS 6/30	3000x1300	30	GS 6/120	3500x1300	120
GS 6/90	2500x1300	90	GS 8/160	3000x1300	160
GS 6/120	2500x1300	120	GS 8/160	3100x1300	160
GS 6/120	2500x1600	120	GS 8/160	3100x1600	160
GS 6/70	3000x1300	70	GS 8/110	3500x1300	110
GS 6/90	3000x1300	90	GS 8/160	3500x1300	160
GS 6/120	3000x1300	120	GS 8/160	3800x1600	160
GS 6/120	3100x1300	120	GS 10/200	3500x1300	200
GS 6/120	3000x1400	120	GS 10/200	3800x1600	200

