

## Perfect Sanding

# UniSander

2.2.2.









### **UniSander**

2.2.2.

2 Sanding heads: – Top, 1 running with /

1 running against

2 Sanding heads: - bottom, 1 running

with / 1 running against

Feed speed: 3 –12 meter / min. Speed sanding heads: 50 – 450 Rpm

Operation side: Right / Left Voltage: 3 \* 400 V, 50 Hz +N+PE

Safety: 32 A

Sucking out: 3000 m³/hour – 25 m/sec

Prepared for line installation.

Item size:

Length: min 250 mm

Height: min 5 mm - max 150 mm Width: 1300 mm up to 2100 mm

#### Dimension of the machine:

Length: 2185 mm Height: 2000 mm Width: 2000 mm

Turbo Blower + Cleaning brushes

Roller table with pressure rollers

Color: 7035

### **Perfect Sanding**

Production/analysis Product/analysis Partners & Customers Experience/test Cross Line Coorperations Flexible solutions Sale Service **Training** Support

## UniSanding Always the best solutions

#### Use:

Top and bottom surface sanding. Finish wood sanding – All types of materials.

Lacquer sanding – All types of lacquer / primer.



UniSanding A/S • Gemsevej 11 • DK-7800 Skive www.unisanding.com • info@unisanding.com T: +45 96 14 28 00