You are always welcome at Friulmac.

We appreciate your interest in our equipment. Please call to make arrangements for a personalized visit. The city of Udine, located in the Italian region called Friuli, is considered the European chair manufacturing center where a concentration of know-how and technology can be found. You will experience how the world's best selling DET and Wood Machining Centers are designed, produced and assembled and how you, our CUSTOMER, stand at the top of our business philosophy.





SEDE CENTRALE HEAD OFFICE FRIULMAC S.p.A. Via delle Industrie - Z.I.U. 33050 Pavia di Udine

Phone +39 0432 655007 r.a. Fax +39 0432 655107 Http://www.friulmac.it

SALES AND SERVICE FOR NORTH AMERICA FRIULMAC Inc. 1264 25" Street Place S.E. Hickory, N.C. 28602 - USA Phone 828/327-6265 Fax 828/327-6273 Toll free number 1 800 282-1690 Http://www.friulmacusa.com E-mail: friulmac@friulmacusa.com





VILLACH

Friulmac

Improve quality and output! Become more flexible!

END TRIM, PROFILE, END-BORE, GLUE & DOWEL, MORTISE, DOVE-TAIL, EDGE-BORE, FACE-BORE... **ENDLESS COMBINATIONS!**

THE BEST EXPRESSION OF FRIULMAC PHILOSOPHY.

A MODULAR STURDY BASE FRAME THAT CAN ACCOMODATE UP TO 5 WORKING STATIONS

PER SIDE ACCORDING TO OUR CUSTOMERS REQUIREMENTS.

Idramat possible configurations.

| | IDRAMAT/E | IDRAMAT/S |
|-----|-----------|-----------|
| 001 | | |
| 002 | | |
| 003 | | |
| 004 | | |
| 005 | | |
| 006 | | |
| 007 | | |
| 800 | おく | |
| 009 | | |

Statements and illustrations in this brochure may include optional equipment. As our policy is to constantly improve design, the details given in this leaflet should not be regarded as binding.

Endless solutions.

Scoring unit "B-2" Beveling unit "B-3" "B-12/45°" Profiling unit "J-2" CNC routing unit "J-3"

CNC profiling unit "J-5"

Profiling unit "L"





Trimming unit "B-8"



Top trimming unit "B-12"



Vertical trimming unit



Bottom trimming unit "B-13"



Jump profiling unit "J-1"







CNC routing unit "J-4"





Hauncing unit "1-2"



End-boring unit "M"



End-boring unit "M/45°"



Face boring unit "N-1"



Back boring unit "0-1"



Bottom boring unit "Q-3"



Glue injection/dowel insering unit "R"



Glue injection/dowel insering unit "R/45°"



Glue injecting unit "R-4"



Glue injecting unit "R-4/45°"



Dowel insering unit "R-5"



Dowel insering unit "R-5/45°"






Idramat technical specifications.

| | IDRAMAT/E | | IDRAMAT/S | |
|---------------------|--|-----------------|--|--|
| Workpiece length | (based on configuration) - 1,000 mm | (BOC) - 39" | 190 - 1,000 mm | 7 31/64" - 39" (at 45° min. 180 mm - 7") |
| Workpiece width | 30 - (based on configuration) | 1 3/16" - (BOC) | 30 - 200 mm | 3/16" - 7 7/8" (at 45" max. 100 mm - 3 15/16") |
| Workpiece thickness | 12 - (based on configuration) | 1/2" - (BOC) | 12 - 45 mm | 15/32" - 1 49/64" |
| Production capacity | 14 - 20 pieces/min. | | Based on parts dimension and machine configuration | |
| | (subject to parts dimension and machine configuration) | | | |

Idramat available options.

| | IDRAMAT/E | IDRAMAT/S |
|--|-----------------------|-----------------------|
| Workpiece max, length increase | Up to 3,000 mm - 118" | Up to 3,000 mm - 118" |
| Quick disconnect profiling spindles system | * | |
| Workpiece return conveyor- system to the operator | | • |
| Sound/safety wing opening Hoods | | |



Non-stop manufacturing.

SPECIAL ATTENTION HAS ALSO BEEN GIVEN TO THE DESIGN.

MECHANIZATIONS

A VARIETY OF PRODUCTS REQUIRES A VARIETY OF SOLUTIONS...THAT WE CAN PROVIDE.

ACCORDING TO THE LEVEL OF AUTOMATION AND PRODUCTION CAPACITY OF THE PLANER/MOULDER AND/OR DET, WE HAVE SEMIAUTOMATIC AS WELL AS FULLY AUTOMATIC LINKING DEVICES TO OFFER. DIFFERENT SOLUTIONS ARE AVAILABLE FOR BOTH LENGTHWISE AND CROSSWISE TRANSPORTATION OF RAW MATERIAL AS WELL AS FINISHED PRODUCTS.

IN DEVELOPING AND MANUFACTURING THE MOST SIMPLE AND EFFICIENT LINKING SYSTEMS,










Just a few examples...



Horizontal CNC ROUTING UNIT "J-4"




DOUBLE EDGE BORING MACHINE "MP-9/B"



Transversally moving SCORING AND TRIMMING UNIT "B-8/B-2"

IDRAMAT

PROFILING UNIT "J-2" with back-up blocks and pneumatic chip-breaker



Detail view of the referencing and clamping system for working units positioned at 45° angle



Vertical CNC ROUTING UNIT "J-3"




QUICK DISCONNECT PROFILING SPINDLE SYSTEM to reduce set-up time and Increase productivity







Vertical PROFILING "I-2"





Any kind of profile. Any!





Our machines, their features.




FLOORMAT

DRAMAT

QUADRAMAT








cut boards continuously to any kind of moulder to save machining time and extend tool life:



Workpieces return conveyor and stacking system to create a one







extreme productivity in the flooring processing.



The most user-friendly double end-cut profiling

the market. Pin-pointed for today's just-in-time





matching machines.
Extreme precision, state of the art technology, super reduced sel-up time, modern design, this is what you expect from your machine investment, this is what Friulmac guarantees offering



cabinet and entry door top-notch quality and profitability. With allows processing of any kind of profile



The only double end-cut profiting machine that makes "just-in-time" easy! Only one operator required, it can process any kind of end profite without tear-out. Extremely user friendly and flexible, it can be provided with end-boring, face boring vertical boring.



The best expression of Friulmac philosophy.

A modular base frame that can accomodate up to 5 working stations per side according to your

End trim, profile, end-bore, glue & dowel, mortise, dove-tail, edge-bore, face-bore... endless



The Quadramat line is designed to process an extremely wide range of operations, for both solid wood and panel products.

All versions of Quadramat are built based on a modular concept to suit all your needs and

